

Page: 1 of 9

January 9, 2009

Product Name Revised: March 10, 2009

TN-210Y, TN-230Y, TN-240Y, TN-270Y Toner Version number: 2

MSDS No. YT402-01-EUUSOTHER

Issued:

## Section 1 – Identification of the Substance/Preparation and of the Company/Undertaking

Product name: TN-210Y Toner, TN-230Y Toner, TN-240Y Toner, TN-270Y Toner

Material name: YT402

Use of Product: These products are yellow toner in a cartridge for Brother Industries, Ltd. laser printers,

multifunction devices and fax receivers.

The cartridge prevents the toner from spilling in normal use.

Manufacturer: Brother Industries, Ltd.

15-1 Naeshiro-cho, Mizuho-ku, Nagoya 467-8561, Japan

Telephone (for information): +81-52-824-2735

Importer in USA: Brother International Corporation

100 Somerset Corporate Boulevard, P.O. Box 6911, Bridgewater, NJ 08807-0911, USA

Telephone (for information): +1-800-284-4329

Importer in Canada: Brother International Corporation (Canada) Ltd.

1 Hotel de Ville, Dollard des Ormeaux, Quebec, H9B 3H6, Canada

Telephone (for information): +1-514-685-0600

Importer in Europe: Brother International Europe Ltd.

Brother House, 1 Tame Street, Guide Bridge, Audenshaw, Manchester M34 5JE, UK

Telephone (for information): +44-161-330-6531

Importer in Australia: Brother International (Aust.) Pty. Ltd. ACN 001 393 835

Level 3, Building A, 11 Talavera Road, Macquarie Park, NSW 2113, Australia

Telephone (for information): +61-2-9887-4344

We do not provide 24-hour cover, for information please telephone the appropriate office during business hours.



**Product Name** 

#### **MATERIAL SAFETY DATA SHEET**

Page: 2 of 9

Issued: January 9, 2009

Revised: March 10, 2009

MSDS No. YT402-01-EUUSOTHER

Version number: 2

TN-210Y, TN-230Y, TN-240Y, TN-270Y Toner

Section 2 - Hazards identification

#### **EMERGENCY OVERVIEW**

These products are the yellow colored toner with an odorless. They are not expected to cause any adverse health or physical effects through normal use. Unintended operations may produce dust leakage that may cause eye and respiratory tract irritation. Toxic combustion products may be released under fire conditions.

### Potential health effects from overexposure:

Possible routes of entry include skin/eye contact and dust inhalation. Minimal respiratory tract irritation may occur as with large amounts of any non-toxic dust. Overexposure to decomposition or combustion products may cause irritation of eyes, skin and respiratory tract. See Section 10 for information on combustion products.

#### EC Classification:

Not classified as hazardous according to EU Directive 1999/45/EC.

#### Australia Classification:

Not classified as hazardous according to the criteria of NOHSC.

### Potential Health Effect:

#### Routes of exposure:

Possible routes of entry include skin/eye contact and dust inhalation.

#### Skin contact:

No symptoms will appear.

#### Eve contact:

Eye irritation will be caused. Use this product as intended in order to prevent the dust leakage that leads to eye contact.

#### Particulate inhalation:

Exposure to large amount of dust will cause lung irritation, difficult breathing, sneezing and/or coughing.

Use this product as intended in order to prevent the dust leakage that leads to dust inhalation.



Issued: January 9, 2009

Page: 3 of 9

Product Name Revised: March 10, 2009

TN-210Y, TN-230Y, TN-240Y, TN-270Y Toner Version number: 2

MSDS No. YT402-01-EUUSOTHER

### Ingestion:

Stomach irritation will be caused. It is highly unlikely that ingestion occurs under intended use.

# Section 3 - Composition / information on ingredients

Chemical name: Styrene-acrylate Toner (Mixture)

#### Ingredients:

Component/ Substance	CAS Number	EC Number	%Wt.	EU Symbol letters / Risk Phrases
Styrene-acrylate Copolymer	25767-47-9		84 - 87	Not classified
Pigment	Registered		5 - 6	Not classified
Fatty Acid Ester	Registered		4 - 6	Not classified
PMMA	9011-14-7		1 - 3	Not classified
Silicon Dioxide (amorphous)	112945-52-5	231-545-4	1 - 3	Not classified
Styrene-acrylic resin	Registered		0.1 - 2	Not classified
Silicon Dioxide (amorphous)	844491-94-7	430-570-1	< 1	Not classified

## Section 4 - First aid measures

If irritation occurs or persists from any route of exposure, remove the affected individual from the area and seek medical assistance.

## Eye contact:

Flush eyes with running water for 15 minutes with eyelids open. Consult an eye-doctor.

### Skin contact:

Remove contaminated clothes and wash skin with soap and water.

#### Particulate inhalation:

Remove the sufferer to fresh air and seek medical assistance immediately.

#### Ingestion:

Seek medical assistance immediately.



Issued:

January 9, 2009

**Product Name** 

Revised:

March 10, 2009

Page: 4 of 9

TN-210Y, TN-230Y, TN-240Y, TN-270Y Toner

Version number: 2

MSDS No. YT402-01-EUUSOTHER

## Section 5 - Fire fighting measures

## Extinguishing media:

Dry chemicals, CO<sub>2</sub>, water spray or foam are recommended media.

# Special firefighting procedures:

Do not use straight water, high-pressure water or water steam in order to prevent creating a dust cloud and spreading fire dust. Use appropriate respirator for carbon monoxide and carbon dioxide. Wear positive pressure self-contained breathing apparatus (SCBA) during the attack phase of firefighting operations and during cleanup in enclosed or poorly ventilated areas immediately after a fire. Personnel not having suitable respiratory protection must leave the area to prevent significant exposure to toxic combustion gases from any source.

## Unusual fire and explosion hazards:

Thermal decomposition of organic components may result in occurrence of oxides of carbon.

Special precautions must be taken if (like most organic materials in powder form) it can form explosive mixtures when dispersed in air. Toxic gasses may be formed upon combustion and represents a hazard to firefighters. See Section 10 for additional information on combustion products.

Explosion limits: Lower =  $65 - 70 \text{ g/m}^3$ 

## Section 6 - Accidental release measures

# Personal precautions:

Minimize generation of toner dust. Avoid inhalation of the dust.

## Environmental precautions:

Prevent from entering into the surface water or sewerage system.

### Method of cleaning up:

Sweep the spilt toner or remove it with a vacuum cleaner, and transfer into the sealed container carefully. Sweep slowly to minimize generation of dust during clean-up. If the vacuum cleaner is used, the motor must be rated as dust explosion-proof. A conductive hose bonded to the machine should be used to reduce static build-up. Residue can be removed with soap and cold water.

Clothes may be washed or dry cleaned after removal of loose toner.

See section 13 for disposal considerations.



Page: 5 of 9

January 9, 2009

Product Name Revised: March 10, 2009

TN-210Y, TN-230Y, TN-240Y, TN-270Y Toner Version number: 2

MSDS No. YT402-01-EUUSOTHER

Issued:

## Section 7 - Handling and storage

## Handling:

Keep out of the reach of children. In case of accidental spill, try not to disperse the particles. Avoid prolonged inhalation of excessive dust and contact eyes. Use with adequate ventilation. Use the mask, which recommended preventing dust and coarse particulate.

## Storage:

Keep out of the reach of children. Keep container tightly closed. Keep away from contact with oxidizing materials. Store in a cool and dry place away from direct light to maintain quality.

## Section 8 - Exposure controls / personal protection

#### Exposure limit value:

Ingredients	CAS Number	OSHA PEL	ACGIH TLV	Workplace exposure limit (UK, basis: EH40/2005)	
				Long-term exposure limit	Short-term exposure limit
				(8-hour TWA	(15-minute TWA
O''. D' ' ' '	044404 04 7	0 / . 3	40 / 3 TIA/A	reference period)	reference period)
Silicon Dioxide	844491-94-7	6 mg/m <sup>3</sup>	10 mg/m <sup>3</sup> TWA	6 mg/m <sup>3</sup>	
(amorphous)			(inhalable dust)	(inhalable dust)	
			3 mg/m <sup>3</sup> TWA	2.4 mg/m <sup>3</sup>	
			(respirable dust)	(respirable dust)	
Silicon Dioxide	112945-52-5		10 mg/m <sup>3</sup> TWA	6 mg/m <sup>3</sup>	
(amorphous)				(inhalable dust)	
				2.4 mg/m <sup>3</sup>	
				(respirable dust)	

## Additional exposure data:

USA OSHA PEL (TWA): 15 mg/m<sup>3</sup> (Total dust), 5 mg/m<sup>3</sup> (Respirable Fraction)

ACGIH TLV (TWA): 10 mg/m³ (Inhalable particles), 3 mg/m³ (Respirable particles)

UK, EH40/2005 (8-hour TWA): 10 mg/m<sup>3</sup> (Inhalable dust), 4 mg/m<sup>3</sup> (Respirable dust)



Issued: January 9, 2009

Page: 6 of 9

Product Name Revised: March 10, 2009

TN-210Y, TN-230Y, TN-240Y, TN-270Y Toner Version number: 2

MSDS No. YT402-01-EUUSOTHER

### Ventilation:

Good general ventilation should be sufficient under normal use.

## Personal protective equipment:

Not required under intended use. For use other than in normal operating procedures (such as in the event of large spill), the following should be applied:

Eye/face: Safety goggles

Skin: Protective gloves recommended

Respiratory: Dust mask (Respirator for large spill)

## Section 9 - Physical and chemical properties

Appearance and odor: Yellow powder and odorless

pH: Not applicable Boiling point/boiling range: Not applicable

Melting point/melting range: 110 °C (softening point)

Flash point: Not applicable

Flammability (solid, gas): No data available

Explosive properties: 65 - 70 g/m³ (Dust explosibility: Lower limit)

Oxidizing properties: No data available Vapour pressure: Not applicable

Relative density: 1.15 (Specific Gravity H<sub>2</sub>0=1)

Solubility: No data available

Water solubility: Negligible

Partition coefficient:n-octanol/water: No data available
Viscosity:

Vapour density:

Not applicable
Evaporation rate:

Not applicable



-

Page: 7 of 9

January 9, 2009

Product Name Revised: March 10, 2009

TN-210Y, TN-230Y, TN-240Y, TN-270Y Toner Version number: 2

MSDS No. YT402-01-EUUSOTHER

Issued:

## Section 10 - Stability and reactivity

Stability: Stable

Hazardous polymerization: Will not occur

Conditions to avoid: Overheating (do not expose to temperature above 200°C) and

contact with ignition sources such as open flames, sparks, electrical

arcs and static discharge sources.

Materials to avoid: Avoid exposure to strong oxidizers or reducing agents.

Hazardous decomposition products: The gas generated by heat decomposition may contain carbon

monoxide, carbon dioxide and Nitrogen.

# Section 11 - Toxicological information

#### **Products**

Acute oral toxicity:  $LD_{50} > 2000 mg/kg$  (Method: OECD#420) Acute inhalation toxicity:  $LC_{50} > 5.15 mg/l$  (Method: OECD#403) Skin irritation: Non-irritant (Method: OECD#404) Eye irritation: Minimal irritant (Method: OECD#405)

Mutagenicity: Negative (Method: OECD#471 / Ames test)

Skin Sensitization (LLNA) Non-sensitizer (Method: OECD#429)

### Section 12 - Ecological information

No data available on the adverse effects of this product on the environment.

Ecotoxicity: No data available
Mobility: No data available
Persistence and degradability: No data available
Bioaccumulation potential: No data available



Issued: January 9, 2009

Page: 8 of 9

Product Name Revised: March 10, 2009

TN-210Y, TN-230Y, TN-240Y, TN-270Y Toner Version number: 2

MSDS No. YT402-01-EUUSOTHER

### Section 13 - Disposal considerations

Do not put toner or toner cartridge into fire. It cause burn injury from spread-fired toner.

When you shred a toner cartridge, do it at dust-explosion prevented place. Finely dispersed particles may form explosive mixtures in air.

Dispose of in compliance with Federal, State and local regulations.

## Section 14 - Transportation information

U.N. Recommendations on the Transport of Dangerous Goods: Not applicable

U.N. Number: None
U.N. Classification: None.

EC Classification: Not classified as hazardous according to EU Directive 1999/45/EC.

Not regulated under DOT, IMDG, ADR, RID, IATA.

- \* DOT: U.S. Department of Transportation
- \* IMDG: International Maritime Dangerous Goods
- \* ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road.
- \* RID: International regulations concerning the international carriage of dangerous goods by rail
- \* IATA: International Air Transport Association

# Section 15 - Regulatory information

Inventories: JCSCL (Japan) Yes

TSCA (USA) Yes EINECS/ELINCS (EU) Yes

Information on the label (according to 1999/45/EC and 67/548/EEC)

Symbol, R-Phrase, S-Phrase: Not required.

Canada Information

WHMIS Controlled Product: Not applicable (Manufactured article)



Page: 9 of 9

Issued:

January 9, 2009

**Product Name** 

Revised:

March 10, 2009

TN-210Y, TN-230Y, TN-240Y, TN-270Y Toner

Version number: 2

MSDS No. YT402-01-EUUSOTHER

## Section 16 - Other information

# Hazard rating system classification

	NFPA	HMIS	Key: 0-least; 1-slight; 2-moderate; 3-high; 4-extreme	
Health	1	1	<u>N</u> ational <u>Fire</u> <u>Protection</u> <u>A</u> ssociation rating identifies hazards	
Flammability	1	1	during a fire emergency. <u>H</u> azardous <u>M</u> aterials <u>I</u> dentification	
Reactivity	0	0	<b>S</b> ystem rating applies to products as packaged.	

### Additional Information;

The information relates only to this specific toner cartridge. It may not be valid for this toner cartridge, if used in combination with any other materials or in any other process. And it is based on our best knowledge as of the date of preparation (revision).